



Application

Manually-operated shut-off nozzle used for gravity and low pressure fueling and water dispensing.

Features and Details

- 35 PSI maximum working pressure
- Heavy duty construction
- **300ALMM** includes arctic mitten expanded handle guard

Materials of Construction

300

- Body and cap... Brass
- Disc... FKM
- Stem... Brass
- O-ring... FKM
- Spout... Brass

300AL

- Body and cap... Aluminum
- Disc... FKM
- Stem... Aluminum
- O-ring... FKM
- Spout... Aluminum

300AL

- Body... Aluminum
- Cap... Stainless steel
- Disc... PTFE
- Stem... Stainless steel
- Packing... PTFE
- Spout... Aluminum

300ALM

- Body... Anodized aluminum
- Cap... Anodized aluminum
- Disc... FKM or FDA Buna-N
- Stem... Stainless steel
- O-Ring... Buna-N
- Spout unleaded... Brass (¹³/₁₆" OD), aluminum (¹³/₁₆" OD)





Certifications and Listings

300ALM

Water nozzles to military drawing #13225E1707 and #13225E9094; Fuel nozzles to CID AA-52030, Type I, Size 1, Class A or B, Style 1

Item Number	Size	Spout	Weight (lbs)
300---3100 AN	3/4"	13/16"	4.25
300---3200 AN	1"	13/16"	4.25
300AL-3100 AN	3/4"	13/16"	2.25
300AL-3200 AN	1"	13/16"	2.25
300AL-3300 AN	3/4"	15/16"	2.25
300AL-3400 AN	1"	15/16"	2.25
300ATS4000 AN	1"	None	2.30
300ATS4400 AN	1"	15/16"	2.50
300ALM0500 AN	1"	13/16"	2.25
300ALM0600 AM	1"	15/16"	2.25
300ALMM100 AN	1"	15/16"	3.0

*Consult Price List for other options.

