

# Model 516 5-Gallon Spill Container

SPECIFICATION SHEET

## Application

Tank top spill containers are designed to contain small spills that occur at the fill point on aboveground storage tanks. The 516 has a hinged cover that is lockable with a padlock. EVR approved models available.

## Materials of Construction

- Body... powder coated white (black powder coat optional)
- Lid... powder coated white (black powder coat optional)
- Other hardware... Zinc plated steel

### Drain (optional)

- Drain push rod... brass
- Drain nut... brass
- Spring... bronze
- O-ring... fluoroelastomer

## Code Compliance

- Florida DEP EQ 725, California Air Resources Board Phase I AST EVR models available, meets the new and revised requirements for CAN-ULC-S663-11 (effective September 25, 2015)



Item Number	A	B	C	D	E	F	G	H	I
516--0200 ACPW	F	2	No	Centered	12 <sup>1</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	17.0	Yes
516--0400 ACPW	F	4	No	Centered	13 <sup>13</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	21.0	Yes
516D--0200 ACPW	F	2	Yes	Centered	13 <sup>9</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	17.0	Yes
516D--0400 ACPW	F	4	Yes	Centered	13 <sup>13</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	21.0	Yes
516O--0200 ACPW	F	2	No	Offset	12 <sup>1</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	17.0	Yes
516O--0400 ACPW	F	4	No	Offset	13 <sup>13</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	21.0	Yes
516O--0400ACEVR	F	4	No	Offset	13 <sup>13</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	21.0	Yes
516OD-0200 ACPW	F	2	Yes	Offset	13 <sup>9</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	17.0	Yes
516OD-0400 ACPW	F	4	Yes	Offset	13 <sup>13</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	21.0	Yes
516M--0200 ACPW	M	2	No	Centered	12 <sup>9</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	16.50	Yes
516M--0400 ACPW	M	4	No	Centered	13 <sup>25</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	19.0	Yes
516MD-0200 ACPW	M	2	Yes	Centered	13 <sup>9</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	17.50	Yes
516MD-0400 ACPW	M	4	Yes	Centered	13 <sup>25</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	20.50	Yes
516MO-0200 ACPW	M	2	No	Offset	12 <sup>9</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	17.0	Yes
516MO-0400 ACPW	M	4	No	Offset	13 <sup>25</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	19.0	Yes
516MO-0400ACEVR	M	4	No	Offset	13 <sup>25</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	19.0	Yes
516MOD0200 ACPW	M	2	Yes	Offset	13 <sup>9</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	17.50	Yes
516MOD0400 ACPW	M	4	Yes	Offset	13 <sup>25</sup> / <sub>32</sub> "	17 <sup>13</sup> / <sub>64</sub> "	13 <sup>13</sup> / <sub>64</sub> "	20.50	Yes

### SPECIFICATION OPTIONS:

- A—Mounting connection: Male (M), Female (F)
- B—Size: NPT threads
- C—Drain: Yes/No
- D—Mount
- E—Height (inches)
- F—Width (inches)
- G—Body diameter (inches)
- H—Shipping weight (lbs)
- I—ULC listing



570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238

t. 563.583.5701 | 800.553.4840 | f. 563.583.5028

www.morbros.com