

FLEX-ING® COMPOSITE ACCESS COVERS

At a fraction of the weight of typical steel access covers, a single technician can easily remove the lightweight FLEX-ING® composite access cover.



HIGHLIGHTS

- Slip resistant covers are constructed of many layers of high quality fiberglass bonded together with premium resin and then hand finished with the utmost attention to quality.
- At their center, our composite access cover tapers up from 1" to 1¼" in wall thickness while most competitive models remain at a uniform 1" wall thickness. The extra wall thickness provides minimal deflection and an extended service life.
- A shallow handle hole and chest-style handle with backer plate keep the wall thickness higher around this high-impact area of the cover.

ORDERING INFORMATION

Composite Access Cover

| Model | Description |
|---------------|--|
| 14U-3810 | 39" composite cover with 37" x 10" skirt |
| 14U-RT3810 | 39" raintight composite cover with 37" x 10" skirt |
| 14U-RT3810CL | 39" raintight composite cover with 37" x 10" skirt and cam locks |
| 14U-RT3810CLC | 39" raintight composite cover |
| 14U-3810C | 39" composite cover |
| 14U-4210 | 44" composite cover with 42" x 10" steel skirt |
| 14U-RT4210 | 44" raintight composite cover |
| 14U-RT4210CL | 44" raintight composite cover with 42" x 10" steel skirt and cam locks |
| 14U-RT4210CLC | 44" raintight composite cover with cam locks |
| 14U-4210C | 44" composite cover |

SPECIFICATIONS

- Exceeds H20 and HS20 load standards (maximum axle load requiring support for the 32,000, or 16,000 pounds for each set of dual tire wheels).
- Available with solid construction cast Zn-Al-Mg alloy, slope-style cam locks for the ultimate in watertight sealing.
- 12 gauge skirt construction that is also powder coated for extreme protection.
- 38" and 42" come standard with spring loaded handle and are available with cam lock for raintight seal.

Dimensions

| Model | Diameter | Lid Thickness | Frame ID | Skirt Height | Skirt ID |
|-------|----------|---------------|----------|--------------|----------|
| 38" | 39" | 1" | 39.25" | 10.75" | 37" |
| 42" | 44" | 1" | 44.25" | 10.75" | 42" |

Note: Confirm clearance of interior dimensions for your application before ordering.