



Product Shown
F-32S-T-F

About the F Series Full-Body

The Bravo F Series full body entry fitting is compatible with both singlewall and doublewall monitored sumps. The F Series is a termination entry fitting which terminates secondary pipe at the exterior of the containment sump. A separate test reducer is not needed to terminate from primary to secondary pipe. The F Series has dual integrated test ports that can be used for testing, drainage to a sensor, or VPH constant monitoring. Models available for both size-over-size and rigid conduit. Quality FRP construction and bonded installation provides an extremely long service life compared to flexible entry fittings.

Bravo Solution Center

Call or Text (323) 541-3851
orders@sbravo.com

SIZES

- ¾", 1"
- 3x2"
- 4x3" FRP Piping
- 6x4"

MATERIAL

- Tank-spec fiberglass

SPECIFICATIONS

- Bonded FRP entry fitting, for long service life
- Available for singlewall and doublewall sumps
- No piping test reducers required
- Dual redundant test ports
- Models for flat and curved sump walls
- 30-year corrosion warranty
- UL2447 Listed



NEW CONSTRUCTION FITTINGS

F Series Full-Body, Flat Sump Wall



Pipe type	Part #	Description
3/4" galvanized conduit	F-07S-0-F	3/4" galvanized conduit, full-body with duel injection ports, EPOXY REQ'D
3/4" PVC coated conduit	F-07RS-0-F	3/4" PVC coated conduit, full-body with duel injection ports, EPOXY REQ'D
3/4" galvanized conduit	F-07S-0-DF	3/4" galvanized conduit, doublewall full-body, duel injection ports and tertiary boot seal, Flat wall FRP, EPOXY REQ'D
3/4" PVC coated conduit	F-07RS-0-DF	3/4" PVC coated conduit, doublewall full-body, duel injection ports and tertiary boot seal, Flat wall FRP, EPOXY REQ'D
1" galvanized conduit	F-10S-0-F	1" galvanized conduit, full-body with duel injection ports, EPOXY REQ'D
1" PVC coated conduit	F-10RS-0-F	1" PVC coated conduit, full-body with duel injection ports, EPOXY REQ'D
1" galvanized conduit	F-10S-0-DF	1" galvanized conduit, doublewall full-body, duel injection ports and tertiary boot seal, Flat wall FRP, EPOXY REQ'D
1" PVC coated conduit	F-10RS-0-DF	1" PVC coated conduit, doublewall full-body, duel injection ports and tertiary boot seal, Flat wall FRP, EPOXY REQ'D
3/4 brass ground- ing rod	F-07-GR	3/4" brass grounding rod, full-body with brass conductor and clamps, EPOXY REQ'D
3 x 2" FRP	F-32S-T-F	3x2" FRP, full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D
4 x 3" FRP	F-43S-T-F	4x3" FRP, full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D
6 x 4" FRP	F-64S-T-F	6x4" FRP, full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D
3 x 2" FRP	F-32A-T-F	3x2" FRP, adjustable full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D
4 x 3" FRP	F-43A-T-F	4x3" FRP, adjustable full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D

F Series Full-Body, Round Sump Wall

Pipe type	Part #	Description
3/4" galvanized conduit	F-07S-0-R	3/4" galvanized conduit, full-body with duel injection ports, EPOXY REQ'D
3/4" PVC coated conduit	F-07RS-0-R	3/4" PVC coated conduit, full-body with duel injection ports, EPOXY REQ'D
3/4" galvanized conduit	F-07S-0-DR	3/4" galvanized conduit, doublewall full-body, duel injection ports and tertiary boot seal, Round wall FRP, EPOXY REQ'D
3/4" PVC coated conduit	F-07RS-0-DR	3/4" PVC coated conduit, doublewall full-body, duel injection ports and tertiary boot seal, Round wall FRP, EPOXY REQ'D
1" galvanized conduit	F-10S-0-R	1" galvanized conduit, full-body with duel injection ports, EPOXY REQ'D
1" PVC coated conduit	F-10RS-0-R	1" PVC coated conduit, full-body with duel injection ports, EPOXY REQ'D
1" galvanized conduit	F-10S-0-DR	1" galvanized conduit, doublewall full-body, duel injection ports and tertiary boot seal, Round wall FRP, EPOXY REQ'D
1" PVC coated conduit	F-10RS-0-DR	1" PVC coated conduit, doublewall full-body, duel injection ports and tertiary boot seal, Round wall FRP, EPOXY REQ'D
3/4 brass ground- ing rod	F-07-GR-R	3/4" brass grounding rod, full-body with brass conductor and clamps, EPOXY REQ'D
3 x 2" FRP	F-32S-T-R	3x2" FRP, full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D
4 x 3" FRP	F-43S-T-R	4x3" FRP, full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D
6 x 4" FRP	F-64S-T-R	6x4" FRP, full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D
3 x 2" FRP	F-32A-T-R	3x2" FRP, adjustable full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D
4 x 3" FRP	F-43A-T-R	4x3" FRP, adjustable full-body taper by slip; dual test ports and single injection port, EPOXY REQ'D